

CV24300XPC C Customer Drawing





SUFFIX "X"			PLUG	
О	CLEAR POLYCARBONATE RX2530 GAMMA	GREEN SILICONE RUBBER CLS2600HR	POLYPROPYLENE H0500HN	
W	CLEAR POLYCARBONATE RX2530 GAMMA	OFF-WHITE SILICONE RUBBER CLS2600HR	POLYPROPYLENE H0500HN	

NOTES:

- CRITICAL DIMENSIONS CIRCLED AND SUBJECT TO INSPECTION. DIMENSIONS IN PARENTHESES FOR REFERENCE ONLY.
- 2. LUER COMPATIBLE WITH ISO 594-1, AND ISO 80369-7.

QUALITY CRITER	IΑ	Ċ
----------------	----	---

O.D. FLASH 0.015 MAX. (0.4mm)

GATE VESTIGE 0.01 MAX. (0.3mm)

EMBEDDED PARTICLES, BUBBLES, SPOTS, STAINS: 0.3mm² MAX. NO MORE THAN 3 PER PART.

	DRAWN BY	DMC	DATE 6/10/16] ///	3 Hallion Dalaceta
	APPROVED BY		DATE] <i>L</i> 7;	ঠ Halkey-Roberts
	MATERIAL	SEE NOT	ΓE	TITLE	,
MOLDED PARTS: GATES, PARTING LINES, AND FLASH PER QUALITY CRITERIA	FINISH				CATHETER VALVE ASSY.
PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS SOLE PROPERTY	UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES TOLERANCES:		THIRD ANGLE PROJECTION	SIZE	CV24300XPC CV24300XPC
OF HALKEY-ROBERTS CORPORATION ST. PETERSBURG, FL. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF HALKEY-ROBERTS CORPORATION IS PROHIBITED.	ANGULAR: ± 1° TWO PLACE DECIM THREE PLACE DECI			SCALE 4:1	DO NOT SCALE DRAWING 1 OF 1